



BCS-NX3004

High-speed CPU with built-in power supply

High-speed processing Cpu, 200 PID loops in 1ms
 Application memory capacity, 3MB
 Persistent memory, 7,5KB
 Max. rack I/O modules, 32
 Com. Interfaces, 1xEthernet/1xSerial
 Fieldbus connection, Profibus DP/Modbus TCP/RTU/OPC UA/DA
 Web server diagnostics

Facts

General description

Article number	66.014.123-9
Warranty	Up to 2 years

Mechanical

Certificates	CE, ROHS, UL, DNV
Module dimensions (W x H x D)	36.00 x 114.63 x 115.30 mm
Net weight	350 g

Power

Current consumption from backplane rack	-
---	---

System

Hot Swap	Yes
One Touch Diag (OTD)	Yes
Status and diagnostics indication	Yes
Redundancy	No
Maximum nbr of expansion racks	1
Maximum nbr of modules	32
Clock synchronization (SNTP)	SNTP
Network monitor (SNMP)	SNMPv1, SNMPv2c, SNMPv3
Program memory	3 MB
Source code memory	32 MB
User files memory	16 MB

Communication

Communication protocols	ModbusTCP client/server, Modbus RTU master/slave, User defined protocol, OPC UA/DA server
Ethernet interface	1xRJ45 10/100 Mbps
Serial interface	1xRS422/485

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

+46 40 35 86 00 (tel:+46 40 35 86 00)

info@beijerelectronics.com (mailto:info@beijerelectronics.com)