



## BCS-NX5001

### PROFIBUS-DP master

Profibus DP V0/V1  
All configuration and parameterization through BCS Tools  
Redundant architecture support  
Hot-Swap  
One touch diagnostics for easy maintenance

## Facts

### General description

Article number	66.014.922-1
Warranty	Up to 2 years

### Mechanical

Certificates	CE, ROHS, UL, DNV
Module dimensions (W x H x D)	36.00 x 114.63 x 115.30 mm
Net weight	200 g

### Power

Current consumption from backplane rack	400 mA
---	--------

### System

Hot Swap	Yes
One Touch Diag (OTD)	Yes
Status and diagnostics indication	Yes
Transmission rate	9.6 to 12.000 kbit/s
Redundancy support	Yes
Application layer	Profibus DP V0/V1
Cable type	Profibus DP cable
Maximum cable length	According to the Profibus DP standard

## **People & Technology. Connected.**

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00](tel:+4640358600) ([tel:+46 40 35 86 00](tel:+4640358600))

[info@beijerelectronics.com](mailto:info@beijerelectronics.com) (<mailto:info@beijerelectronics.com>)