



BCS-NX5210

PROFIBUS-DP slave

Redundant Profibus DP slave module
Hot-Swap of I/O modules
Automatic baud rate detection
Ability to use up to 20 I/O modules in a single rack
Local advanced diagnostic service

Facts

General description

Article number	66.014.927-2
Warranty	Up to 2 years

Mechanical

Certificates	CE, ROHS, UL, DNV
Module dimensions (W x H x D)	36.00 x 114.63 x 115.30 mm
Net weight	200 g

System

Hot Swap	Yes
One Touch Diag (OTD)	Yes
Status and diagnostics indication	Yes
Transmission rate	9.6 to 12.000 kbit/s
Redundancy support	Yes
Application layer	Profibus DP V0
Cable type	Profibus DP cable
Maximum cable length	According to the Profibus DP standard

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00 \(tel:+46 40 35 86 00\)](tel:+4640358600)

[info@beijerelectronics.com \(mailto:info@beijerelectronics.com\)](mailto:info@beijerelectronics.com)