BoX2 base v2

IoT gateway

Protocol conversion
Cloud connectivity
HMI and web server
Local data base storage, alarm servers, data exchange, reporting, C# scripting
IP20
-10 °C to +50 °C

Facts

General description

Part number	100-1362
Life cycle status	Active
Warranty	Up to 2 years

Features

Protocol conversion	Yes
Cloud connectivity	Yes
HMI web server	Yes
Local data base storage	Yes
C# scripting	Yes
Alarm server	Yes

Certifications

General	CE, FCC, KCC

Mechanical

Mounting option	DIN rail

Power

Input voltage	24VDC (18-32V DC)
Power consumption (max)	4W
Input fuse	3 AT

System

CPU	ARM Cortex A8 600 MHz
RAM	512MB
FLASH	2GB SSD(eMMC), 1.5GB free for application

Serial communication

Number of serial ports	2 Port 9pin DSUB
Serial port 1	RS32 (RTS)/RS422/RS485
Serial port 2	RS 232/RS422/Rs485
Serial port 3	RS32 (RTS)/RS422/RS485
Serial port 6	RS 232/RS422/Rs485

Ethernet communication

Number of Ethernet ports	2
Ethernet port 1	1x10/100 Base-T (shielded RJ45)
Ethernet port 2	1x10/100 Base-T (shielded RJ45)

Expansion interface

SD card	uSD
USB	2xUSB 2.0 500mA

Environmental

Operating temperature	-10°C to +50°C
Storage temperature	-20° to +60°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP20
Sealing back	IP20
Humidity	5% – 85% non-condensed
Altitude (max)	< 3000m

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

+46 40 35 86 00 (tel:+46 40 35 86 00)

info@beijerelectronics.com (mailto:info@beijerelectronics.com)