



GT-4334

4 analog outputs

4-20 mA

12 bit resolution

Load resistance: Min. 550 Ω - Max. 750 Ω

18pt removable terminal block

Facts

General description

Article number	100-8196
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: ±1.6mm, 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: 0.0125g ² /Hz, 40 ~ 100 Hz: 0.0125 → 0.002g ² /Hz, 100 ~ 500 Hz: 0.002 g ² /Hz, 500 ~ 2000 Hz: 0.002 → 1.3 x 10-4g ² /Hz, Test time: 1hrs for each test
Industrial emissions	EN 61000-6-4/A11: 2011
Industrial immunity	EN 61000-6-2: 2019
Installation position	Horizontal, Vertical
Product certifications	CE, UL, cUL, FCC, RoHS, China RoHS, Reach
Power dissipation	Max. 30 mA @ 5 VDC
Isolation	I/O to Logic: Photocoupler isolation, I/O to Field Power: Non-Isolation
Module size	12x109x70 mm

Environmental

Mounting	35mm DIN rail
Operating temperature	-20 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-20 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Analog output module specifications

Calibration	Not Required
Common type	10 common, field power 0 V is common (AGND)
Conversion time	≤0.15 ms, all channels
Data format	16 bit Integer (2 ¹⁶ compliment)
Diagnostics	Field Power OFF: LED BLINK
Indicators	1 Green G-Bus status
Load resistance	Min. 550 Ω, max. 750 Ω
Output format	4 ~ 20 mA
Outputs per module	4 channels single ended, non-isolated between channel
Resolution in ranges	12 bits: 3.91 uA/bit

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00](tel:+4640358600) ([tel:+46 40 35 86 00](tel:+4640358600))

info@beijerelectronics.com (<mailto:info@beijerelectronics.com>)