



GT-2348

8 digital outputs

24 VDC / 2 A
Transistor SOURCE
10pt removable terminal block

 [Important life cycle dates, read more ->](#)

Facts

General description

Article number	100-8193
Warranty	Up to 2 years
Article status	EOL
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: $\pm 1.6\text{mm}$, 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: $0.0125\text{g}^2/\text{Hz}$, 40 ~ 100 Hz: $0.0125 \rightarrow 0.002\text{g}^2/\text{Hz}$, 100 ~ 500 Hz: $0.002\text{ g}^2/\text{Hz}$, 500 ~ 2000 Hz: $0.002 \rightarrow 1.3 \times 10\text{-}4\text{g}^2/\text{Hz}$, Test time: 1hrs for each test
Industrial emissions	EN 61000-6-4/A11: 2011
Industrial immunity	EN 61000-6-2: 2019
Installation position	Horisontal, Vertical
Product certifications	CE, UL, cUL, FCC, RoHS, China RoHS, Reach
Power dissipation	Max. 40 mA @ 5 VDC
Isolation	I/O to Logic: Photocoupler isolation, I/O to Field Power: Non-Isolation
Field power	Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~30 VDC, 70°C: 18~26.4 VDC
Weight	57 g
Module size	12x99x70 mm

Environmental

Mounting	35mm DIN rail
Operating temperature	-20 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-20 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Digital output module specifications

Indicators	8 green output status
Outputs per module	8 point SOURCE
Output current rating	Refer to Specification of NA: GT9xxx: Max. 2 A per channel / Max. 10 A per unit. GL9xxx: Max. 2 A per channel / Max. 8 A per unit.
Output signal delay	OFF to ON: Max. 0.1 ms, ON to OFF: Max. 0.9 ms
ON state min current	Min. 1 mA
Output voltage range	Nominal supply voltage: 24 VDC, Min. 15 VDC to Max. 30 VDC
ON state voltage	3.0 VDC @ 2 A
OFF state leakage current	Max. 3uA
Common type	8 point / 2 COM
Protection	None

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00 \(tel:+46 40 35 86 00\)](tel:+4640358600)

[info@beijerelectronics.com \(mailto:info@beijerelectronics.com\)](mailto:info@beijerelectronics.com)