



GL-9073

Modbus RTU adapter

2 x Serial RJ45

Up to 16 expansion slices

Small slice type (light version)

5pt removable terminal block (CNT-8412)

Facts

General description

Article number	100-8115
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: $\pm 1.6\text{mm}$, 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: $0.0125\text{g}^2/\text{Hz}$, 40 ~ 100 Hz: $0.0125 \rightarrow 0.002\text{g}^2/\text{Hz}$, 100 ~ 500 Hz: $0.002\text{ g}^2/\text{Hz}$, 500 ~ 2000 Hz: $0.002 \rightarrow 1.3 \times 10^{-4}\text{g}^2/\text{Hz}$, Test time: 1hrs for each test
Industrial emissions	EN 61000-6-4/A11: 2011
Industrial immunity	EN 61000-6-2: 2019
Installation position	Horizontal, Vertical
Product certifications	CE, UL, cUL, FCC, RoHS, China RoHS, Reach
System power	Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~32 VDC, 70°C: 18~26.4 VDC, Output current limitation: 1.5 A, Reverse polarity protection
Power dissipation	Max. 20 mA @ 24 VDC
Current for IO module	1.5 A @ 5 VDC
Isolation	System power to internal logic: Non-Isolation , System power I/O driver: Isolation
Field power	Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~32 VDC, 70°C: 18~26.4 VDC, * Field Power Range is different depending on IO Module series. Refer to IO Module's Specification.
Max current field power contact	DC 8 A max
Weight	75 g
Module size	22x109x70mm

Communication

Station type	Slave
IO data size	128 bytes/slice
Max length bus line	1200 m
Max network nodes	99 nodes
Baud rate	1200 / 2400 / 4800 / 9600 / 19200 / 38400 / 57600 / 115200bps
Settable node address	1 ~ 99 by DIP-switches
Bus connection	2 x RJ45
Indicator	4 Status LEDs, 1 Green/Red, Module Status (MOD) , 1 Green, Current Communication Status (RUN) , 1 Red, Error Status (ERR) , 1 Green/Red, Expansion I/O Module Status (IOS)
Module location	Starter module left side
Field power detection	~14 VDC

Environmental

Mounting	35mm DIN rail
Operating temperature	-20 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-20 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00](tel:+4640358600) ([tel:+46 40 35 86 00](tel:+4640358600))

info@beijerelectronics.com (<mailto:info@beijerelectronics.com>)