



## GL-9087

### PROFINET adapter

2 x Ethernet 10/100Mbps

Up to 10 expansion slices

Small slice type (light version)

5pt removable terminal block (CNT-8412)

## Facts

### General description

Article number	100-8113
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: $\pm 1.6\text{mm}$ , 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: $0.0125\text{g}^2/\text{Hz}$ , 40 ~ 100 Hz: $0.0125 \rightarrow 0.002\text{g}^2/\text{Hz}$ , 100 ~ 500 Hz: $0.002\text{ g}^2/\text{Hz}$ , 500 ~ 2000 Hz: $0.002 \rightarrow 1.3 \times 10^{-4}\text{g}^2/\text{Hz}$ , Test time: 1hrs for each test
Industrial emissions	EN 61000-6-4/A11: 2011
Industrial immunity	EN 61000-6-2: 2019
Installation position	Horisontal, Vertical
Product certifications	CE, UL, cUL, FCC, RoHS, China RoHS, Reach
System power	Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~32 VDC, 70°C: 18~26.4 VDC, Output current limitation: 1.5 A, Reverse polarity protection
Power dissipation	Max. 40 mA @ 24 VDC
Current for IO module	1.5 A @ 5 VDC
Isolation	System power to internal logic: Non-Isolation , System power I/O driver: Isolation
Field power	Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~32 VDC, 70°C: 18~26.4 VDC, * Field Power Range is different depending on IO Module series. Refer to IO Module's Specification.
Max current field power contact	DC 8 A max
Weight	75 g
Module size	22x109x70mm

### Communication

Station type	Slave
IO data size	Input 128bytes / Output 128bytes
Max length bus line	100 m
Max network nodes	Limited by Profinet Specification
Baud rate	100Mbps, Auto-negotiation, Full duplex
Bus connection	2 x RJ45
Indicator	4 LEDs , 1 Green/Red, Module Status (MOD) , 1 Green, Physical Connection (NET) , 1 Green, Exchange Data/Traffic Present (ERR) , 1 Green/Red, Expansion I/O Module Status (IOS) , , 2 LEDs (each RJ45 Connector) , 1 Yellow, Link/Active , 1 Green, Not used
Module location	Starter module left side
Field power detection	~14 VDC

## Environmental

Mounting	35mm DIN rail
Operating temperature	-20 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-20 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

## People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00](tel:+4640358600) ([tel:+46 40 35 86 00](tel:+4640358600))

[info@beijerelectronics.com](mailto:info@beijerelectronics.com) (<mailto:info@beijerelectronics.com>)