




GT-5221

Serial interface RS422

1 channel
1200 ~ 115 200 bps
10pt removable terminal block

Facts

General description

Article number	100-8033
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: $\pm 1.6\text{mm}$, 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: $0.0125\text{g}^2/\text{Hz}$, 40 ~ 100 Hz: $0.0125 \rightarrow 0.002\text{g}^2/\text{Hz}$, 100 ~ 500 Hz: $0.002\text{g}^2/\text{Hz}$, 500 ~ 2000 Hz: $0.002 \rightarrow 1.3 \times 10^{-4}\text{g}^2/\text{Hz}$, Test time: 1hrs for each test
Industrial emissions	EN 61000-6-4/A11: 2011
Industrial immunity	EN 61000-6-2: 2019
Installation position	Horizontal, Vertical
Product certifications	CE, UL, cUL, FCC, RoHS, China RoHS, Reach
Power dissipation	Max. 85 mA @ 5 VDC, 0 mA @ 24 VDC
Isolation	I/O to Logic: Photocoupler isolation, I/O to Field Power: Non-Isolation
Field power	Not used. Field power bypassed to next expansion module.
Weight	60 g
Module size	12x99x70 mm

Environmental

Mounting	35mm DIN rail
Operating temperature	-20 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-20 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Communication module specification

Bit distortion	N/A
Cable length	1 km twisted pair
Cable type	Shielded cable recommended
Connection	10 RTB
Data bit	8bit
Data buffer	IO user data 14 bytes, IO size changed max. 63 bytes, Control / status 1 byte, Rx/Tx length 1 byte
Flow control	N/A
Low signal voltage	N/A
High signal voltage	N/A
Line impedance	120 Ω
Input image size	16 bytes (default)@ max. 63 bytes
Output image size	16 bytes (default)@ max. 63 bytes
Parity bit	None / Odd / Even (default: None)
RXD buffer	1024bytes
Stop bit	1bit, 2bit (*Default: 1bit)
Transfer rate	1200 ~ 115200bps
TXD buffer	1024bytes

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmö, SWEDEN

[+46 40 35 86 00](tel:+4640358600) (tel:[+46 40 35 86 00](tel:+4640358600))

info@beijerelectronics.com (mailto:info@beijerelectronics.com)