



PWS5610T-S

 [Important life cycle dates, read more ->](#)

Facts

General description

Part number	300-52501
Life cycle status	Limited
Warranty	1 year

Certifications

General	CE, FCC
---------	---------

Mechanical

Mechanical size	195.0 x 145.0 x 59.1 mm
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	185.8 x 135.8 mm
Weight	0.92 kg
Housing material	Plastic, Gray

Power

Input voltage	24V DC $\pm$ 15%
Power consumption (max)	24VDC, 8W
Input fuse	Internal DC fuse

Display

Size diagonal	5.7" diagonal
Resolution	320x240 pixels
Backlight	LED Backlight
Backlight life time	50000 hours
Backlight brightness	400 cd/m2
Backlight dimming	None
Display type	Color TFT LCD

Serial communication

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS232/RS422/RS485 without RTS/CTS
Serial port 2	RS232/RS422/RS485 without RTS/CTS

Environmental

Operating temperature	-10°C to +60°C
Storage temperature	0°C to +50°C
Shock	10 G, 11 ms 3 times in each direction of X-, Y- and Zaxes
Vibration	0.5 mm displacement, 10-55 Hz, 2 hours per X-, Y and Z-axis directions
Sealing front	IP65
Humidity	20 - 90% RH non-condensed

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00](tel:+4640358600) (tel:[+46 40 35 86 00](tel:+4640358600))

info@bejjerelectronics.com (mailto:info@bejjerelectronics.com)