



PWS5A00T-P

10.4" graphic touch HMI, plus

64k color
TFT display
COM Port x3
CF card
USB host x2
USB device x1
800 480 pixels

i [Important life cycle dates, read more ->](#)

Facts

General description

Part number	300-51602
Life cycle status	Limited
Warranty	1 year

Certifications

General	CE, FCC
---------	---------

Mechanical

Mechanical size	297.0 x 222.0 x 52.3 mm
Number of touches	1million finger touch operations.
Touch type	Resistive
Cut-out size	286.0 x 211.0 mm
Weight	2.38 kg
Housing material	Plastic, Gray

Power

Input voltage	24V DC \pm 15%
Power consumption (max)	24VDC, 30W
Input fuse	Internal DC fuse

Display

Size diagonal	10.1" diagonal
Resolution	800x480 pixels
Backlight	LED Backlight
Backlight life time	20000 hours
Backlight brightness	300 cd/m2
Backlight dimming	None
Display type	Color TFT LCD

Serial communication

Number of serial ports	2 Port 9pin DSUB/1 Port 25pin DSUB
Serial port 1	RS232/RS485
Serial port 2	RS 232/RS422/Rs485
Serial port 3	RS422/485

Expansion interface

SD card	CF
USB	2 USB Host, 1 USB Device

Environmental

Operating temperature	-10°C to +60°C
Storage temperature	0°C to +50°C
Shock	10 G, 11 ms 3 times in each direction of X-, Y- and Zaxes
Vibration	0.5 mm displacement, 10-55 Hz, 2 hours per X-, Yand Z-axis directions
Sealing front	IP65
Humidity	10~90% RH(0 °C~40 °C),10~60% RH(41 °C~50 °C),noncondensed.

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

+46 40 35 86 00 (tel:+46 40 35 86 00)

info@bejerelectronics.com (mailto:info@bejerelectronics.com)