



## PWS6300S-S

160 x 80 pixel keypad HMI

16 shades of gray  
STN display  
COM Port x1  
160 x 80 pixels

**i** [Important life cycle dates, read more ->](#)

## Facts

### General description

Part number	300-53101
Life cycle status	Limited
Warranty	1 year

### Certifications

General	CE, FCC, UL
---------	-------------

### Mechanical

Mechanical size	173.0 x 105.5 x 51.8 mm
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	160.8 x 93.3 mm
Weight	0.68 kg
Housing material	Plastic, Gray

## Power

Input voltage	24V DC $\pm$ 15%
Power consumption (max)	24VDC, 8W
Input fuse	Internal DC fuse

## Display

Size diagonal	3" diagonal
Resolution	160x80 pixels
Backlight	LED Backlight
Backlight life time	50000 hours
Backlight brightness	35 cd/m2
Backlight dimming	None
Display type	Mono STN LCD

## Serial communication

Number of serial ports	1 Port 9pin DSUB
Serial port 2	RS 232/RS422/RS485

## Environmental

Operating temperature	-10°C to +60°C
Storage temperature	0°C to +50°C
Shock	10 G, 11 ms 3 times in each direction of X-, Y- and Zaxes
Vibration	0.5 mm displacement, 10-55 Hz, 2 hours per X-, Y and Z-axis directions
Sealing front	IP65
Humidity	20 - 90% RH non-condensed

## People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmö, SWEDEN

+46 40 35 86 00 (tel:+46 40 35 86 00)

[info@bejjerelectronics.com](mailto:info@bejjerelectronics.com) (mailto:info@bejjerelectronics.com)