



## iX T7B

7" graphic touch HMI with iX runtime

7" TFT-LCD touch screen.

800 × 480 (16:9)

Application storage 1.4 GB

Operating temperature -10 to +50 °C

CE and UL508 approvals

 [Important life cycle dates, read more ->](#)

## Facts

### General description

|                   |              |
|-------------------|--------------|
| Part number       | 640000102    |
| Life cycle status | Discontinued |
| Warranty          | 1 year       |

### Mechanical

|                  |                        |
|------------------|------------------------|
| Mechanical size  | 204 x 143 x 52.2 mm    |
| Touch type       | Resistive type         |
| Weight           | 0.9 kg                 |
| Housing material | Powder coated aluminum |

### Power

|                         |                              |
|-------------------------|------------------------------|
| Input voltage           | +24 VDC (18 - 32 VDC)        |
| Power consumption (max) | 14 W                         |
| Input fuse              | Internal DC fuse, 3.15A slow |

## Display

|                      |                  |
|----------------------|------------------|
| Size diagonal        | 7.0 inch         |
| Resolution           | 800 x 480 pixels |
| Backlight            | LED backlight    |
| Backlight life time  | 50,000 hrs       |
| Backlight brightness | 500 cd/m2        |
| Backlight dimming    | Industrial       |
| Display type         | TFT LCD          |

## Serial communication

|                        |   |
|------------------------|---|
| Number of serial ports | 2 Port combined 9pin DSUB with dual pin out |
| Serial port 1          | RS 232 (RTS/CTS)                            |
| Serial port 2          | RS422/485                                   |
| Serial port 3          | RS 232                                      |
| Serial port 4          | RS422 (RTS)/RS485                           |

## Ethernet communication

|                          |                                      |
|--------------------------|--------------------------------------|
| Number of Ethernet ports | 2                                    |
| Ethernet port 1          | 1x10/100 Base-T (shielded RJ45)      |
| Ethernet port 2          | 1x10/100/1000 Base-T (shielded RJ45) |

## Environmental

|                       |                     |
|-----------------------|---------------------|
| Operating temperature | -10 to + 50 °C      |
| Storage temperature   | -20 to + 70 °C      |
| Shock                 | 10G 11ms half sine  |
| Vibration             | 0,7G RMS            |
| Sealing front         | IP65                |
| Sealing back          | IP20                |
| Humidity              | <85 % non-condensed |

## People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmö, SWEDEN

[+46 40 35 86 00 \(tel:+46 40 35 86 00\)](tel:+4640358600)

[info@beijerelectronics.com \(mailto:info@beijerelectronics.com\)](mailto:info@beijerelectronics.com)

