



X2 extreme 12

12" Rugged HMI with iX runtime

- 1280 × 800 pixel (16:10)
- TFT-LCD touch screen
- 1.5 GB application memory
- Ethernet 1x100 Mbit
- 30°C to +70°C operating temperature
- DNV GL, KR, LR, ABS, CCS, BV, NK marine approvals
- UL Class I Div 2, ATEX/IECEX Zone 2,22, CNEX

Facts

General description

Part number	640014305
Life cycle status	Active
Warranty	Up to 2 years

Certifications

General	CE, FCC, KCC, UL 61010-2-201, UL 746C
Hazardous	UL C1D2, IECEx (Zone2), ATEX (Zone2), ATEX (Zone22), IECEx (Zone22), CNEX
Marine	KR, LR, ABS, CCS, BV, NK, DNV GL

Mechanical

Mechanical size	340 x 242 x 69mm
Mounting option	Panel Mount
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	324 x 226mm
Weight	2.8 kg
Housing material	Powder-coated aluminum, Black

Power

Input voltage	24 VDC (18 to 32 VDC) CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4. UL and cUL: The power supply must conform with the requirements for class 2 power supplies.
Power consumption (max)	16 W
Input fuse	Internal DC fuse

System

Hardware platform	X2 extreme
CPU	i.MX6DualLite, Dual Cortex-A9 800MHz 512kBL2cache
RAM	1 GB
FLASH	2GB SSD(eMMC), 1.5GB free for application

Display

Size diagonal	12.1" diagonal
Resolution	1280x800 pixels
Backlight	LED Backlight
Backlight life time	70000 hours
Backlight brightness	500 cd/m2
Backlight dimming	Marine optimized dimming
Display type	TFT-LCD with LED backlight

Serial communication

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/RS485/CAN

Ethernet communication

Number of Ethernet ports	1
Ethernet port 1	1x10/100 Base-T (shielded RJ45)

Communication CAN

Number of CAN ports	1
CAN port 1	1 Mbit

Expansion interface

SD card	SD and SDHC
USB	2xUSB 2.0 500mA

Environmental

Operating temperature	-30°C to +70°C
Storage temperature	-40°C to +80°C
Shock	40g, half-sine, 11ms according to IEC60068-2-27
Vibration	4g, according to IEC 60068-2-6, Test Fc
Sealing front	IP66, NEMA 4X/ 12 and UL Type 4X/ 12
Sealing back	IP20
Humidity	5% – 95% non-condensed
Altitude (max)	< 3000m

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a
SE - 211 75 Malmö, SWEDEN

+46 40 35 86 00 (tel:+46 40 35 86 00)
info@bejjerelectronics.com (mailto:info@bejjerelectronics.com)