



## X2 extreme 15

15" Rugged HMI with iX runtime

1280 × 800 pixel (16:10)

TFT-LCD touch screen

1.5 GB application memory

Ethernet 1x100 Mbit

-30°C to +70°C operating temperature

DNV GL, KR, LR, ABS, CCS, BV, NK marine approvals

UL Class I Div 2, ATEX/IECEx Zone 2,22, CNEX

## Facts

### General description

Part number	640014605
Life cycle status	Active
Warranty	Up to 2 years

### Certifications

General	CE, FCC, KCC, UL 61010-2-201, UL 746C
Hazardous	UL C1D2, IECEx (Zone2), ATEX (Zone2), ATEX (Zone22), IECEx (Zone22), CNEX
Marine	KR, LR, ABS, CCS, BV, NK, DNV GL

### Mechanical

Mechanical size	410 x 286 x 73mm
Mounting option	Panel Mount
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	394 x 270mm
Weight	4.1 kg
Housing material	Powder-coated aluminum, Black

## Power

Input voltage	24 VDC (18 to 32 VDC) CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4. UL and cUL: The power supply must conform with the requirements for class 2 power supplies.
Power consumption (max)	18 W
Input fuse	Internal DC fuse

## System

Hardware platform	X2 extreme
CPU	i.MX6DualLite, Dual Cortex-A9 800MHz 512kBL2cache
RAM	1 GB
FLASH	2GB SSD(eMMC), 1.5GB free for application

## Display

Size diagonal	15.4" diagonal
Resolution	1280x800 pixels
Backlight	LED Backlight
Backlight life time	50000 hours
Backlight brightness	450 cd/m2
Backlight dimming	Marine optimized dimming
Display type	TFT-LCD with LED backlight

## Serial communication

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/RS485/CAN

## Ethernet communication

Number of Ethernet ports	1
Ethernet port 1	1x10/100 Base-T (shielded RJ45)

## Communication CAN

Number of CAN ports	1
CAN port 1	1 Mbit

## Expansion interface

SD card	SD and SDHC
USB	2xUSB 2.0 500mA

## Environmental

Operating temperature	-30°C to +70°C
Storage temperature	-40°C to +80°C
Shock	40g, half-sine, 11ms according to IEC60068-2-27
Vibration	4g, according to IEC 60068-2-6, Test Fc
Sealing front	IP66, NEMA 4X/ 12 and UL Type 4X/ 12
Sealing back	IP20
Humidity	5% – 95% non-condensed
Altitude (max)	< 3000m

## People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00 \(tel:+46 40 35 86 00\)](tel:+4640358600)

[info@beijerelectronics.com \(mailto:info@beijerelectronics.com\)](mailto:info@beijerelectronics.com)