

# **MPC-3000 Series Hardware User Manual**

---

**Version 1.1, September 2025**

[www.moxa.com/products](http://www.moxa.com/products)



## **MPC-3000 Series Hardware User Manual**

The software described in this manual is furnished under a license agreement and may be used only in accordance with the terms of that agreement.

### **Copyright Notice**

© 2025 Moxa Inc. All rights reserved.

### **Trademarks**

The MOXA logo is a registered trademark of Moxa Inc.  
All other trademarks or registered marks in this manual belong to their respective manufacturers.

### **Disclaimer**

- Information in this document is subject to change without notice and does not represent a commitment on the part of Moxa.
- Moxa provides this document as is, without warranty of any kind, either expressed or implied, including, but not limited to, its particular purpose. Moxa reserves the right to make improvements and/or changes to this manual, or to the products and/or the programs described in this manual, at any time.
- Information provided in this manual is intended to be accurate and reliable. However, Moxa assumes no responsibility for its use, or for any infringements on the rights of third parties that may result from its use.
- This product might include unintentional technical or typographical errors. Changes are periodically made to the information herein to correct such errors, and these changes are incorporated into new editions of the publication.

### **Technical Support Contact Information**

[www.moxa.com/support](http://www.moxa.com/support)

## Table of Contents

<b>1. Introduction .....</b>	<b>5</b>
Package Checklist .....	5
Product Features .....	5
MPC-3000 Hardware Specifications .....	5
<b>2. Hardware Introduction .....</b>	<b>6</b>
Appearance.....	6
Dimensions.....	9
Display Control Buttons .....	12
<b>3. Hardware Installation and Connections.....</b>	<b>13</b>
Hardware Installation .....	13
Panel Mounting .....	13
VESA Mounting (optional).....	15
Communication Connections .....	16
DC Power Input.....	16
Connecting to the Network .....	17
Connecting to a Serial Device .....	17
Digital Inputs/Digital Outputs.....	18
Connecting to a USB Device.....	19
Installing a CFast or SD Card .....	19
Real-time Clock .....	19
Powering On/Off the MPC-3000 .....	20
Grounding the MPC-3000 .....	20
<b>4. BIOS Setup .....</b>	<b>21</b>
Entering the BIOS Setup.....	21
Main Page.....	23
Advanced Settings .....	23
Boot Configuration.....	24
SATA Configuration .....	25
CPU Configuration .....	26
Video Configuration .....	27
Chipset Configuration.....	28
Console Redirection .....	29
SIO ITE8786E.....	30
Hardware Monitor.....	31
Security Settings .....	32
Current TPM Device .....	32
TPM State.....	32
Clear TPM.....	32
Set Supervisor Password .....	33
Power Settings .....	35
Wake on LAN .....	35
Auto Wake on S5 .....	35
Boot Settings .....	36
Network Stack .....	36
PXE Boot capability.....	36
USB Boot .....	36
Timeout .....	37
EFI .....	37
Exit Settings .....	38
Exit Saving Changes .....	38
Save Change Without Exit .....	38
Exit Discarding Changes.....	38
Load Optimal Defaults.....	38
Load Custom Defaults .....	39
Save Custom Defaults.....	39
Discard Changes .....	39
Administering Secure Boot.....	39
Enabling UEFI Secure Boot .....	40

Enroll EFI Image .....	40
Enroll Customer Key .....	41
Upgrading the BIOS .....	42
<b>A. Regulatory Approval Statement.....</b>	<b>47</b>

# 1. Introduction

---

The MPC-3000 Series panel PCs with dual-core x6211E or quad-core x6425E processor deliver a reliable, durable, and versatile platform for use in industrial environments. With two software selectable RS-232/422/485 serial ports and two Gigabit Ethernet ports, the MPC-3000 Series panel PCs support a wide variety of serial interfaces as well as high-speed IT communications, all with native network redundancy. Both regular and wide-screen models are available to meeting the display needs of various field applications.

## Package Checklist

Each model is shipped with the following items:

- 1 MPC-3000 Series panel PC
- 1 2-pin terminal block for DC power input
- 1 10-pin terminal block for DIO
- 1 2-pin terminal block for remote power switch
- Panel-mounting kit
- Quick installation guide (printed)
- Warranty card



### NOTE

Notify your sales representative if any of the above items are missing or damaged.

## Product Features

MPC-3000 panel PCs come with the following features:

- Panels of various screen sizes
- Intel Atom® x6211E dual-core or x6425E quad-core processor
- -30 to 60°C operation temperature, fanless and without a heater
- 400 / 1000 nit sunlight-readable LCD
- Glove-friendly, multi-touch screen
- Class 1 Division 2, ATEX Zone 2, and IECEx compliant
- 12/24 VDC power input

## MPC-3000 Hardware Specifications



### NOTE


The latest specifications for Moxa's products can be found at <https://moxa.com>.

## 2. Hardware Introduction


This chapter introduces the hardware design of the MPC-3000 Series, including the appearance and dimensions of various models. In addition, we also introduce the peripherals used by the MPC-3000 panel PCs to enable easy installation at diverse field sites.

### Appearance


#### MPC-3070W Models




#### MPC-3100 Models




## MPC-3120 Models




## MPC-3120W Models



## MPC-3150 Models




## MPC-3150W Models



# Dimensions


## MPC-3070W Models

Unit: mm (inch)




## MPC-3100 Models

Unit: mm (inch)




## MPC-3120 Models

Unit: mm (inch)




## MPC-3120W Models

Unit: mm (inch)




## MPC-3150 Models

Unit: mm (inch)




## MPC-3150W Models

Unit: mm (inch)



# Display Control Buttons

The MPC-3000 is provided with three display-control buttons on the right panel.



The display-control buttons can be used as described in the following table.

Symbol and Name	Usage	Function
 Power	Press	Power on OR Enter sleep or hibernation mode OR Wake up <b>NOTE:</b> You can modify the function of the Power button in the OS settings menu
	Press and hold for 4 seconds	Power off
 Brightness +	Press	Manually increase the brightness of the panel
 Brightness -	Press	Manually decrease the brightness of the panel

### 3. Hardware Installation and Connections

In this chapter, we describe how to install the MPC-3000 and connect the MPC-3000 to the network and to various devices.

#### Hardware Installation




##### ATTENTION

To avoid damage to equipment, all installations must be done by skilled personnel.


#### Panel Mounting

A panel-mounting kit, consisting of 6 (MPC-3070W), 7 (MPC-3100), 10 (MPC-3120/3120W), 11 (MPC-3150W), or 12 (MPC-3150) mounting clamps, is included in the MPC-3000 package. The dimension tolerance and the cabinet space required to panel mount the MPC-3000 is illustrated in the following diagrams:




Series	A (mm)	B (mm)	C (mm)	D (mm)	R (mm)	Mounting Kits (pcs)
MPC-3070W		53.0	193.3	133.3		6
MPC-3100		66.3	242.0	192.0		7
MPC-3120	Min. 4.5 Max. 8.0	66.2	281.4	220.5	6.5 ±0.5	10
MPC-3120W		68.2	298.0	203.0		10
MPC-3150		66.2	350.0	276.0		12
MPC-3150W		68.2	381.0	237.0		11

To install the panel-mounting kit on the MPC-3000, insert the mounting clamps in the mounting holes provided on the rear panel and slide the clamps to the ends of the panel as shown in the following figures:



Use a torque of 5 kgf-cm to secure the mounting screws to fasten the panel-mounting kit onto the wall.

**Screw M4x25mm SUS with Cushion  
(Fix Torque Needed: 5 kgf-cm)**



Ensure that there is adequate space behind the panel for ventilation, and that the panel material and thickness can support the weight of the device.

## VESA Mounting (optional)




### ATTENTION


VESA mounting is not applicable to the marine applications.

The VESA-mounting installation dimensions are as follows:


**MPC-3070W**




**MPC-3100**




**MPC-3120**



**MPC-3120W**






Series	Compass Safe Distance
MPC-3070W	400 mm
MPC-3100	400 mm
MPC-3120	600 mm
MPC-3120W	700 mm
MPC-3150	700 mm
MPC-3150W	800 mm

## Communication Connections

### DC Power Input


The MPC-3000 uses a DC power input. To connect the power source to the 2-pin terminal block, use the 60-W power adapter as shown in the following diagram. The terminal block is available in the accessories package.

The required wire size is 12-18 AWG (wire type: Cu) and a torque value 0.5 N·m (4.425 lb-in) is recommended.



## Connecting to the Network

The pin assignments for the two Fast Ethernet 10/100/1000 Mbps RJ45 ports are shown in the following table:




Pin	10/100 Mbps	1000 Mbps
1	ETx+	TRD(0)+
2	ETx-	TRD(0)-
3	ERx+	TRD(1)+
4	-	TRD(2)+
5	-	TRD(2)-
6	ERx-	TRD(1)-
7	-	TRD(3)+
8	-	TRD(3)-

The LEDs on the LAN ports indicate the following:

LAN 1/LAN 2 (indicators on the connectors)	Green	100 Mbps Ethernet mode
	Yellow	1000 Mbps Gigabit Ethernet mode
	Off	No activity / 10 Mbps Ethernet mode

## Connecting to a Serial Device

The MPC-3000 offers two software-selectable RS-232/422/485 serial ports over a DB9 connector. The pin assignments for the ports are shown in the following table:




**RS-232/422/485 Pinouts**

Pin	RS-232	RS-422	RS-485 (4-wire)	RS-485 (2-wire)
1	DCD	TxD(-)	TxD(-)	-
2	RxD	TxD(+)	TxD(+)	-
3	TxD	RxD(+)	RxD(+)	DataB(+)
4	DTR	RxD(-)	RxD(-)	DataA(-)
5	GND	GND	GND	GND
6	DSR	-	-	-
7	RTS	-	-	-
8	CTS	-	-	-

## Digital Inputs/Digital Outputs

The MPC-3000 is provided with a DIO port, which is a 10-pin terminal block that includes 4 DIs and 4 DOs as illustrated in the following figure.

**DI 1 2 3 4 GND**




Digital Voltage: 30 VDC

Digital Output: 10 mA (Single port)


DIO terminal block (plug matched with socket) with wire size 30 and torque value 0.5 N-m (4.425 lb-in)

**DO 1 2 3 4 COM**

**DI Dry Contact**




**DI Wet Contact**



**DO Contact**

**Sink**



# Connecting to a USB Device

Two USB 3.0 ports are available on the bottom panel. Use these ports to connect mass-storage drives and other peripherals.

## Installing a CFast or SD Card

The MPC-3000 provides two storage options—CFast and SD card. The storage slots are located on the right panel. You can install the OS on the CFast card and save your data into the SD card.

To install the storage devices, do the following:

1. Remove the 2 screws holding the storage-slot cover to the MPC-3000.
2. Remove the cover and locate the SD and CFast card slots.



3. Reattach the cover and secure it with screws.

## Real-time Clock

The real-time clock (RTC) is powered by a lithium battery. We strongly recommend that you do not replace the lithium battery without help from a qualified Moxa support engineer. If you need to change the battery, contact the Moxa RMA service team. The contact details are available at:

[http://www.moxa.com/rma/about\\_rma.aspx](http://www.moxa.com/rma/about_rma.aspx).



### ATTENTION

There is a risk of explosion if the clock's lithium battery is replaced with an incompatible battery. Dispose of used batteries according to the Instructions.

# Powering On/Off the MPC-3000

Connect a **Terminal Block to Power Jack Converter** to the MPC- 3000 terminal block and connect a 60 W power adapter to the converter. Supply power through the power adapter. After you have connected a power source, the system Power button turns on automatically. It takes about 10 to 30 seconds for the system to boot up. You can change the power-on behavior of your panel PC by changing the BIOS settings.

To power off the MPC-3000, we recommend using the "shut down" function provided by the OS installed on the MPC. If you use the **Power** button, you may enter one of the following states depending on the power management settings in the OS: standby, hibernation, or system shutdown mode. If you encounter problems, you can press and hold the **Power** button for 4 seconds to force a hard shutdown of the system.

In addition, the MPC-3000 panel PCs come with 2-pin terminal block for remote power control.



## WARNING

The 2-pin remote power terminal block is not for use in hazardous locations.



## ATTENTION


This equipment is intended to be supplied by an external power source, which is evaluated according to UL/EN/IEC 62368-1 or UL/IEC 60950-1. The power source shall comply with ES1/SELV and LPS requirements, output rating is 12 VDC, 5.6 A (min.) or 24 VDC, 2.8 A (min.), and an ambient temperature of 60°C minimum.

If you are using a Class I adapter, the power cord should be connected to an outlet with an earthing connection.

# Grounding the MPC-3000

Proper grounding and wire routing help to limit the effects of noise from electromagnetic interference (EMI). Run the ground connection from the ground screw to the grounding surface prior to connecting the power source.

The minimum cross-sectional area required for the protective earthing conductor is 3.31 mm<sup>2</sup>. A mandatory external bonding facility with a cross-sectional area of at least 4 mm<sup>2</sup> must be installed for effective conductivity.



## 4. BIOS Setup

---


In this chapter, we describe the BIOS settings for the MPC-3000 panel PC. The BIOS is a set of input/output control routines for peripherals to initialize the basic settings. The BIOS helps boot the system before the operating system is loaded. The BIOS setup allows the user to modify the system configuration for basic input/output peripherals. All the configurations are stored in the CMOS RAM, which has a backup battery in case the panel PC is not connected to a power source. Consequently, the data stored in the CMOS RAM is retained when the system is rebooted, or the power is disconnected.

### Entering the BIOS Setup

To enter the BIOS setup utility, press the F2 key while the system is booting up. The main BIOS Setup screen will appear. You can configure the following settings on this screen.

- **Continue:** Continue to boot up
- **Boot Manager:** Select the device for boot up
- **Device Management:** Enter the device configuration menu
- **Boot From File:** Select the UEFI boot up file
- **Administer Secure Boot:** Enter the Secure Boot menu
- **Setup Utility:** Enter the BIOS configuration menu


Select **F2** to enter the **BIOS configuration**.



When you enter the **Setup Utility**, a basic description of each function key is listed at the bottom of the screen. Refer to these descriptions to learn how to use them.

<b>F1</b>	<b>General Help</b>	<b>↑ ↓ .</b>	<b>Select Item</b>
<b>F5/ F6</b>	<b>Change Values</b>	<b>↔</b>	<b>Select Menu</b>
<b>F9</b>	<b>Setup Defaults</b>	<b>ESC</b>	<b>Exit</b>
<b>F10</b>	<b>Save and Exit</b>	<b>ENTER</b>	<b>Select or go to Submenu.</b>

The BIOS configuration screen will be shown when you enter the **Setup Utility** option.




## NOTE

The **Processor Type** information may vary depending on the model that you have purchased.


# Main Page

The **Main** page displays basic hardware information, such as model name, BIOS version, and CPU type.



# Advanced Settings


Select the **Advanced** tab in the main menu to open the advanced features screen.



## Boot Configuration


The **Numlock** option allows configuration of the Numlock value

Options: On (default), Off.



# SATA Configuration

This section allows you to select the SATA speed limit and hot plug setting.



## SATA Speed Limited

Options: Gen 1, Gen 2, Gen 3 (default)

## Serial ATA Port


This setting displays information on the installed drives.

## SATA Port Hot Plug

This setting allows you to enable/disable hot-plugging capabilities (the ability to remove the drive while the panel PC is running) that are configured by software for installed storage drives.

Options: Disabled (default), Enabled

# CPU Configuration



## Active Processor Cores

This item indicates the number of cores to enable in each processor package (Cores number depended on the processor).


Options: All (default), 1, 2, 3

## Turbo Mode

Enable/Disable processor Turbo Mode (not supported in models with Intel® Celeron® ).

Options: Disabled, Enabled (default)

# Video Configuration



## DVMT Pre-Allocated

This item allows you to configure pre-allocated memory capacity for the IGD. Pre-allocated graphics memory is invisible to the operating system.

Options: 64M (default), 96M, 128M, 160M

**DVMT:** The amount of video memory your panel PC has depends on the amount of pre-allocated memory set for your system plus the Dynamic Video Memory Technology (DVMT). DVMT dynamically allocates system memory for use as video memory creating the most efficient use of available resources for maximum 2D/3D graphics performance.


## DVMT Total Gfx Mem.

This item allows you to configure the maximum amount of memory DVMT will use when allocating additional memory for the internal graphics device.

Options: 256 MB (default), 128 MB, Max.

# Chipset Configuration

This section allows you to configure the chipset settings.



## Power ON after Power Failure

This item allows you to enable/disable the panel PC from automatically powering up after system power is re-enabled.

Options: ON (default), OFF, Last State

## Load Default After Cleaning RTC Battery

System will load default when detecting RTC battery loss.

Options: Disabled, Enabled (default)


## DO-X Level

This item allows users to set the DO to high or low.

Options: High (default), Low

# Console Redirection

This section allows you to configure the console redirection settings.



## Console Serial Redirect

When the Console Redirection Function is enabled, the console information will be sent both to the display monitor and the serial port (COM1).

Options: Disabled (default), Enabled

# SIO ITE8786E

This section allows users to configure SIO settings.

InsydeH20 Setup Utility Rev. 5.0

Advanced

IT8786E Chip 1 I/O Configuration Port ▶UART Port 1 Configuration ▶UART Port 2 Configuration ▶Hardware Monitor	2Eh/2Fh	UART Configuration
---	---------	--------------------

F1 Help      F5/F6 Change Values      F9 Setup Defaults  
Esc Exit      F7/F8 Select Item      Enter Select ▶ SubMenu      F10 Save and Exit

InsydeH20 Setup Utility Rev. 5.0

Advanced

UART Port 1 Configuration	Configure UART Port using options : [Disabled] Disable device [Enabled] Enable device and use below settings
---------------------------	--

UART Port 1      <Enabled>  
Base I/O Address      <3F8h>  
Interrupt      <IRQ4>  
UART Mode      <RS232>

F1 Help      F5/F6 Change Values      F9 Setup Defaults  
Esc Exit      F7/F8 Select Item      Enter Select ▶ SubMenu      F10 Save and Exit

## UART Port 1

This function allows users to configure the resources for the UART port 1.

Disable: Disable the UART port 1 connection

Enable: Enable the UART port 1 connection (default)

## UART Port 2

This function allows users to configure the resources for the UART port 2.

Disable: Disable the UART port 2 connection

Enable: Enable the UART port 2 connection (default)




### NOTE

All other UART ports can only be configured by an OS utility.


## Hardware Monitor

This section allows you to view stats such as CPU and system temperature, voltage levels, and other chipset information.



# Security Settings

This section allows users to configure security-related settings with a supervisor password.



## Current TPM Device

This item shows if the system has TMP device and its type.

## TPM State

This item allows you view the status of current TPM settings.


## Clear TPM

This item allows users to remove all TPM context associated with a specific owner.


# Set Supervisor Password

This item allows you to set the supervisor password. Select the **Set Supervisor Password** option and enter the password and confirm the password again.

To delete the password, select the **Set Supervisor Password** option and enter the old password; leave the new password fields blank, and then press enter.



After setting the supervisor password, users can choose when the input password screen should be displayed.



Enable: System will ask for the password on post time

Disable: System will ask for the password to go to the setup utility

Config-Only: System will only ask for the password when you select the config (F2) option

# Power Settings

This section allows users to configure power settings.



## Wake on LAN

This feature is used to wake the system by a LAN device from a remote host.

Options: Enabled (default), Disabled


## Auto Wake on S5

This item allows you to configure the panel PC to wake from S5 status. S5 stands for Soft Off, where the PSU remains engaged but power to all other parts of the system is cut. Auto-wake on S5 schedules a soft-reboot at certain periodic times that may be specified in the BIOS.

Options: Disabled (default); By Every Day (user specifies a regular daily time when the panel PC will power up); By Day of Month (user specifies a regular day each month when the panel PC will power up)

# Boot Settings

This section allows users to configure boot settings.



## NOTE

If you do not add any storage, you will not see the EFI option.

## Network Stack

It deploys an Internet Protocol (IP) stack. The IP stack provides an application library to open/close connections to remote devices and send/receive data between the remote devices.

Options: Disabled (default), Enabled

## PXE Boot capability

This item will be shown only when you have enabled the Network Stack.

PXE Booting is booting a system over a network. This item allows users to start PXE over IPv4 or IPv6

Options: Disabled (default), UEFI: IPv4, UEFI: IPv6, UEFI: IPv4/IPv6

## USB Boot

Set booting to USB boot devices capability.


Options: Enabled (Default), Disabled

## Timeout

This item allows users to set the number of seconds that the firmware will wait before booting from the default boot selection.


## EFI

This item allows users to select the boot order. Use F5 (move down) or F6 (move up) to change the boot order.



# Exit Settings

The section allows users to exit the BIOS environment.



## Exit Saving Changes

This item allows you to exit the BIOS environment and save the values you have just configured.

Options: Yes (default), No

## Save Change Without Exit

This item allows you to save changes without exiting the BIOS environment.

Options: Yes (default), No

## Exit Discarding Changes

This item allows you to exit without saving any changes that might have been made to the BIOS.

Options: Yes (default), No

## Load Optimal Defaults

This item allows you to revert to the factory default BIOS values.

Options: Yes (default), No

## Load Custom Defaults

This item allows you to load custom default values for the BIOS settings.

Options: Yes (default), No

## Save Custom Defaults

This item allows you to save the current BIOS values as a “custom default” that may be reverted to at any time by the load custom defaults selection.

Options: Yes (default), No


## Discard Changes

This item allows you to discard all settings you have just configured.

Options: Yes (default), No

## Administering Secure Boot

Press F2 to go to the Administer Secure Boot.



Secure Boot helps panel PCs resist attacks and infection from malware. The feature defines an interface between the operating system and BIOS. It detects tampering with boot loaders, key operation system files, and unauthorized option ROMs by validating their digital signatures.


## Enabling UEFI Secure Boot


Set as “enabled” in “Restore Secure Boot to Factory Settings” under Administer Secure Boot menu. Press F10 as save and exist.



Moxa has included the Microsoft key in the BIOS by default. If you cannot boot up the panel PC using a non-Windows OS, use the following examples.


## Enroll EFI Image






1. Enter **Administer Secure Boot** and select the option **Select a UEFI file as trusted for execution**.
2. Enter the loader name followed by the UEFI standard \EFI\BOOT\BOOT{machine type short-name}.  
E.g., efi\boot\BootX64.efi, Debian (EFI\debian\grubx64.efi), Suse (EFI\opensuse\grubx64.efi)

## Enroll Customer Key





Enter "DB OPTION" and enroll your key. Please make sure your key is CRT format and uses RSA 2048 or better.

## Upgrading the BIOS

This section describes how to upgrade the BIOS on your panel PC.




### NOTE

It is possible to permanently damage the panel PC when upgrading the BIOS. We strongly recommend that you contact Moxa's technical support staff for assistance to obtain all the necessary tools and the most current advice before attempting to upgrade the BIOS on any Moxa device.


## Step 1: Create a Bootable USB Disk

Before upgrading the BIOS, you must create a bootable USB drive as a system boot device for use in the future.


1. Insert a USB disk in the panel PC's USB drive.
2. Search for "format" and select **Create and format hard disk partitions**.



3. Right-click on the USB disk item and select **Format**.



4. Select **FAT32** and click **OK** to start formatting the disk.




## Step 2: Prepare the Upgrade File

You must use the BIOS upgrade installation file to upgrade the BIOS. Contact Moxa's technical department for assistance. The BIOS upgrade file includes an **efi** folder and an **xxxx.efi** file. Copy the **efi** folder and **xxxx.efi** file to the bootable USB disk.

## Step 3: Run the Upgrade Program on Your Panel PC

1. Reboot the panel PC with the boot disk and press F2 to go to the Boot Manager.  
If the BIOS cannot recognize the USB drive as a boot-up device, the USB drive might not have a partition table. Use the Windows command line tool **diskpart** to rebuild the partition table.
2. Select the USB Disk.



The screen will switch to the SHELL environment.

3. Type **fs0:**, go to the directory where the upgrade file is located, and type **xxxxxx.efi** (the file name is based on the upgrade file from Moxa).

```
Device mapping table
fs0   :Removable HardDisk - Alias hd24s0b blk0
        PciRoot(0x0)/Pci(0x14, 0x0)/USB(0x12, 0x0)/HD(1, MBR, 0x00DD3D80, 0x3F, 0xEB5FC1)
blk0  :Removable HardDisk - Alias hd24s0b fs0
        PciRoot(0x0)/Pci(0x14, 0x0)/USB(0x12, 0x0)/HD(1, MBR, 0x00DD3D80, 0x3F, 0xEB5FC1)
blk1  :Removable BlockDevice - Alias <null>
        PciRoot(0x0)/Pci(0x14, 0x0)/USB(0x12, 0x0)
hd24s0b :Removable HardDisk - Alias fs0 blk0
        PciRoot(0x0)/Pci(0x14, 0x0)/USB(0x12, 0x0)/HD(1, MBR, 0x00DD3D80, 0x3F, 0xEB5FC1)


Shell> fs0:
fs0:\> xxxxxxx.efi
```

Wait until the upgrade procedure is completed.




## ATTENTION

Do NOT switch off the power supply during the BIOS upgrade, since doing so may cause the system to crash.




When the upgrade is completed, the panel PC will reboot automatically.

You can check the BIOS version on the Main page to confirm the upgrade.



If the system has more than one boot device, you will see more than one fsx (x represents the number).



4. Go to each fsx (x stands for the number) and type ls to view the content of the boot device. If you find an upgrade file, run it.

```
fs0:\> fs1:  
fs1:\> ls  
Directory of: fs1:\  
  
06/27/19 11:43a <DIR>          16,384  efi  
06/13/19 11:10a          17,974,704  820C100$16 efi  
 1 File(s)  17,974,704 bytes  
 1 Dir(s)
```

## A. Regulatory Approval Statement

---



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

**Class A:** FCC Warning! This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his or her own expense.



**European Community**

**Warning:**

This is a class A product. If used in a domestic environment, this product may cause undesirable radio interference, in which case the user may be required to take adequate measures to prevent the interference from affecting nearby devices.